

Description

FEDERATED OEM PSF 3/1G

Inspection Information	Test Method	Typical Value
Gravity, °API	ASTM D287	33.03
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.86
Flash Point, °C	ASTM D92	204
Flash Point, °F	ASTM D92	400
Viscosity at 40°C, cSt	ASTM D445	34.17
Viscosity at 100°C, cSt	ASTM D445	6.991
Viscosity Index	ASTM D2270	170
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	14,297
Color	ASTM D1500	1.5
Rust Protection	ASTM D665A	Pass

Claims Information

Allison C-4, C-3, C-2	Recommended For
CAT TO-2	Recommended For
Chrysler MS 5931F, P/N 04883077	Recommended For
Chrysler MS-5931	Recommended For
Dexron III G/H, Dexron II D/E, Dexron, AW1	Recommended For
Ford M2C128-C and D	Recommended For
Ford M2C195-A	Recommended For
Ford Mercon, Ford ESP-M2C166-H	Recommended For
GM 9985010	Recommended For
GM 9985010 Saginaw Power Steering System	Recommended For
MB 236.1, Allison V-730D	Recommended For
Type A	Recommended For