

**Description**

FEDERATED MV ATF 12/1QT

<b>Inspection Information</b>	<b>Test Method</b>	<b>Typical Value</b>
Gravity, °API	ASTM D287	33.02
Specific Gravity at 60°F (15.6°C)	ASTM D4052	0.8601
Viscosity at 40°C, cSt	ASTM D445	35.43
Viscosity at 100°C, cSt	ASTM D445	7.56
Viscosity Index	ASTM D2270	189
Pour Point, °C (°F)	ASTM D5950	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	ASTM D2983	11,300
Color	ASTM D1500	Red

## Claims Information

Allison C-4	Recommended For
Audi G 052 025, 052 162, 055 025	Recommended For
BMW 7045E, LA2634, LT71141	Recommended For
BMW P/N 83 22 0 024 359, ETL-8072B	Recommended For
BMW P/N 83 22 0 0246 922, ETL-7045E	Recommended For
BMW P/N 83 22 0 403 249, ETL-8072B	Recommended For
BMW P/N 83 22 9 407 765, LA 2634	Recommended For
BMW P/N 83 22 9 407 807, LT 711 41	Recommended For
Chrysler 05127382AA, 68043742AA, 68157995AA, 68157995AB, 68171866AA	Recommended For
Chrysler AS68RC, Diamond SP-III	Recommended For
Dexron III G/H, Dexron II D/E, Dexron, AW1	Recommended For
Esso LT 71141	Recommended For
Ford Mercon V (XT-5-QM,XT-5-DM)	Recommended For
Ford Mercon, Ford ESP-M2C166-H	Recommended For
Ford P/N XT-2-DX (MERC), Ford P/N XT-2-SM (SYN MERC)	Recommended For
Ford XT8QAW	Recommended For
Fuchs 3353	Recommended For
Honda ATF Ultra II, DW-1, Z-1, 3.0, 3.1	Recommended For
Hyundai NWS 9638	Recommended For
Hyundai/Kia/Mitsubishi Diamond ATF-MA1, ATF PA, AW, J2, J3, SK, SP-II, SP-III, RED-1, SP-IV (00232-1904/04500-00115), SP-IV M (SP4-M), SPH-IV, SP-IV-RR, JWS 3314,	Recommended For
IDEMITSU APOROIL ATF HP, Idemitsu K17 3100 PL085	Recommended For
ISUZU 08200-9001 / Genuine ATF	Recommended For
Jaguar P/N WSS-M2C922-A-1	Recommended For
JWS 3309, Any 3309	Recommended For
JWS 3324	Recommended For
MAN 339 Type Z1, Z2, V1	Recommended For
Mazda ATF M-III, MV, T-IV	Recommended For
MB236.1,2,5,6,7,9, 10, 11	Recommended For
MINI P/N 83 22 0 402 413	Recommended For
Nissan Matic-D, J, K, 402	Recommended For
SAAB P/N 22 717 466, 93 165 147 (AW-1)	Recommended For
Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF, Saturn VI, 21005966, 1940700, 1940767, 22717466,88900925, 93160393,	Recommended For
Shell 3403 M115	Recommended For
Shell 3403, LA2634, Texaco 7045-E, ETL-8072B	Recommended For
Subaru ATF, ATF-HP	Recommended For
Suzuki 3314, 3317	Recommended For
Texaco N402	Recommended For
Toyota T-II, T-III, T-IV, WS	Recommended For

## Claims Information

Type A	Recommended For
Voith 55.6335 (G607)	Recommended For
Volvo P/N 1161540-8	Recommended For
Volvo Passenger Car (4 / 6 sp), Volvo 97340, 97341, 97342	Recommended For
VW G 052 162, 052 162 A1 A2 A6, 099, 055 025 A2	Recommended For
VW P/N GUS 000 162	Recommended For
Highline Warren Recommends this product as Recommended For in applications specifying Allison TES-389	Recommended For
ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C	Recommended For
ZF TE-ML 14B	Recommended For